

Russell Hendrix



DEPENDABLE
SERIES



HABCO QUALITY
Commercial
Refrigerators
and Freezers

Dependable Series™ Refrigerators and Freezers are designed and manufactured to the highest commercial standards.

Russell▶Hendrix has identified key features that commercial applications demand and coupled them with the HABCO® legacy of quality design and manufacturing to provide a complete commercial refrigeration package.

Energy-Balanced™ for optimum efficiency and performance, the Dependable Series™ is the quality choice for commercial reach-in applications.

Dependable Series™ Reach-Ins are designed for dedicated 15 amp circuit operation. Easy Mount door system provides on-location swing door reversal with hold open for loading and swing back protection. Standard solid door locks are reversible on location, while glass door locks are optional. Cleaning and relocation is secure and easy with included commercial casters.

Refrigerators are digitally controlled to maintain stabilized product temperature between 1°C and 3.3°C (33.8°F and 38°F). High efficiency LED display lighting and insulated Low-E glass are standard features on glass door models. Top riding, Easy-Glide sliding door system features insulated door track, nylon tired roller bearings and magnetic seals. Solid door models are equipped with Auto-Actuated Interior Light.

Freezers are digitally controlled to maintain stabilized product holding temperature between -23°C and -20°C (-9.4°F and -4°F). Automatic defrost can also be activated manually. Auto-Actuated Interior Light and Cooling Fan Delay on door opening are standard features.

DEPENDABLE SERIES™ PREMIUM FEATURES

- Digital Controller with Audible/Visual Alarm
- Energy Efficient and precise with peace of mind built-in.
- Stainless Steel Interior and Xterior™ Commercial Stainless Steel stands up to rigours of everyday wear and tear. (White Interior with SST Floor on Glass Doors.)
- Coated Cooling Coil protects from acidic foodstuffs.
- Exclusive, Automatic Stainless Steel Condensate Control System Energy saving, recycles heat from cabinet to control condensate and increase performance.
- Recessed Door Handles eliminates the hassle and damage of exterior mounted handles on solid door models.
- Finless Condenser Coil (Wide-Finned, Lint-Tolerant Coil on SF46SA) virtually eliminates costly repairs due to accumulation of grease and lint.
- Coved Corner Interior for sanitary ease of cleaning.
- ProductTemp™ Control and Temperature Display Controls refrigeration and displays according to simulated average product temperature to a display resolution of 1°C.



HABCO Exclusive Cassette® is standard equipment on Dependable Series™ Refrigerators.

Long respected for quality, performance and value, the Cassette® self-contained refrigeration system ensures return on investment long after your purchase.

Simply remove the Cassette® from work area for maintenance, cleaning or service and enjoy minimal interruption while maintaining a more sanitary environment.

Completely Front Breathing, Dependable Series™ Refrigerators can be placed near rear wall saving valuable aisle space while providing easy access to refrigeration system for maintenance and service.



COMMERCIAL REFRIGERATORS



SE24HCSA Refrigerator/Single Solid Door
*NSF-7 Approved for Open Food Storage



SE46HCSA Refrigerator/Double Solid Door
*NSF-7 Approved for Open Food Storage



SE24HCSXG Refrigerator/Single Glass Door
*NSF-7 Approved for Open Food Storage

COMMERCIAL REFRIGERATOR - SLIDER



SE42HCSXG Refrigerator/Double Sliding Glass Door
*NSF-7 Approved for Open Food Storage

COMMERCIAL FREEZERS



SF24HCSA Freezer/Single Solid Door



SF46HCSA Freezer/Double Solid Door

COMMERCIAL REFRIGERATORS – STAINLESS STEEL XTERIOR™ AND INTERIOR

SOLID SWING DOOR

MODEL	DOORS	SHELF	LOCKS	WIDTH ¹		DEPTH ²		HEIGHT ⁵		COLD SPACE™	ENERGY VOLUME		COOLING CAPACITY	ELECTRICAL ⁷	SHIP WEIGHT	
				MM	IN	MM	IN	MM	IN		LITRES	CU.FT			KG	LBS
SE24HCSA	1	3	STD	607	23 7/8	788	31	1982	78	24	519.9	18.36	1/4	115V / 60 Hz / 3.1A	133	292
SE46HCSA	2	6	STD	1207	47 1/2	788	31	1982	78	46	1039.8	36.7	1/4	115V / 60 Hz / 4.3A	208	458

COMMERCIAL REFRIGERATORS – STAINLESS STEEL XTERIOR™

GLASS SWING DOOR

MODEL	DOORS	SHELF	LOCKS	WIDTH ¹		DEPTH ²		HEIGHT ⁵		COLD SPACE™	ENERGY VOLUME		COOLING CAPACITY	ELECTRICAL ⁷	SHIP WEIGHT	
				MM	IN	MM	IN	MM	IN		LITRES	CU.FT			KG	LBS
SE24HCSXG	1	3	OPT	607	23 7/8	788	31 ³	1982	78	24	530.9	18.75	1/4	115V / 60 Hz / 3.1A	118	258

GLASS SLIDING DOOR

SE42HCSXG	1	6	OPT	1207	47 1/2	788	31 ⁴	1982	78	42	1017.1	35.9	1/4	115V / 60 Hz / 4.3A	194	426
-----------	---	---	-----	------	--------	-----	-----------------	------	----	----	--------	------	-----	---------------------	-----	-----

COMMERCIAL FREEZERS – STAINLESS STEEL XTERIOR™ AND INTERIOR

SOLID SWING DOOR

MODEL	DOORS	SHELF	LOCKS	WIDTH ¹		DEPTH ⁶		HEIGHT ⁵		COLD SPACE™	ENERGY VOLUME		COOLING CAPACITY	ELECTRICAL ⁷	SHIP WEIGHT	
				MM	IN	MM	IN	MM	IN		LITRES	CU.FT			KG	LBS
SF24HCSA	1	3	STD	607	23 7/8	788	31	1982	78	24	449.4	15.87	1	115V / 60 Hz / 6.8A	153	336
SF46HCSA	2	6	STD	1207	47 1/2	788	31	1982	78	46	1003.3	35.43	1	115V / 60 Hz / 7.3A	229	504

SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE.

MILLIMETRES ROUNDED UP TO NEAREST WHOLE MM

¹ Add 19mm (3/4") for casters. ² Add 26mm (1") for power cord. ³ Add 40mm (1 1/2") for door handle. ⁴ Add 13mm (1/2") for header panel.

⁵ Add 121mm (4 3/4") for casters. ⁶ Add minimum 51mm (2") space at rear for heat exchange air-flow. ⁷ Commercial refrigerators and freezers are designed for maximum duty and require dedicated 15 amp electrical circuits to maintain warranty.



SE24HCSA/HCSXG/SF24HCSA RH

SE42HCSXG RH

SE46HCSA/SF46HCSA RH



Features

	SE24HCSXG	SE42HCSXG	SE24HCSA	SE46HCSA	SF24HCSA	SF46HCSA
	Glass Door		Solid Door			
Digitally Controlled	■	■	■	■	■	■
> Audible/Visual Temperature Alarms	■	■	■	■	■	■
> Automatic, Time-Initiated, Temperature Terminated Defrost	-	-	-	-	■	■
> Manual Defrost Enable	-	-	-	-	■	■
> Short Cycle Protection	■	■	■	■	■	■
ProcuTemp™ Refrigeration Control and Display	■	■	■	■	■	■
> Controls and Displays Temperature according to Simulated Average Product Temperature	■	■	■	■	■	■
> Short-Cycle Protection	■	■	■	■	■	■
Stainless Steel Xterior™ Front and Sides	■	■	■	■	■	■
Stainless Steel Interior with Coved Corners	-	-	■	■	■	■
White Interior with Coved Corners	■	■	-	-	-	-
Stainless Interior Floor with Coved Corners	■	■	■	■	■	■
Cassette® refrigeration	■	■	■	■	-	-
> Front Breathing and Venting	■	■	■	■	-	-
> Self-Contained and Fully Removable from Front	■	■	■	■	-	-
Traditional Split-System Refrigeration	-	-	-	-	■	■
> Front Breathing, Rear Venting	-	-	-	-	■	■
> Front Slide-Out High-Side, non-Removable	-	-	-	-	■	■
Finless, Free&Clear™, Non-Clogging, Condenser Coil	■	■	■	■	■	-
> Enduring Energy Efficiency	■	■	■	■	■	-
> Premium Component Lifecycle Protection	■	■	■	■	■	-
Lint-Tolerant Wide Spaced Fin-Type Condenser Coil	-	-	-	-	-	■
Fan Delay on Door Opening	-	-	-	-	■	■
Priority Air-Flow Interior	■	■	■	■	-	-
Priority Air-Flow Exterior	■	■	■	■	■	■
Corrosion Resistant Coated Cooling Coil	■	■	■	■	■	■
Automatic, Stainless Steel Condensate Control System	■	■	■	■	■	■
Premium Unit Bearing Motors	■	■	■	■	■	■
LED Interior Lighting with Switch	■	■	-	-	-	-
Incandescent Interior Lighting Auto-Actuated with Door Opening	-	-	■	■	■	■
Door Lock(s)	□	□	■	■	■	■
Casters Swivel, Two Locking Five (5) Inch	■	■	■	■	■	■
Recessed Door Handles	-	-	■	■	■	■
Reversible Door, On-Location	■	■	■	-	■	-
Reversible Lock, On-Location	□	-	■	-	■	-
Low-E Door Glass	■	■	-	-	-	-
Magnetic Swing Door Gasket(s)	■	-	■	■	■	■
Easy-Glide, Suspended Sliding Doors	-	■	-	-	-	-
> Nylon Tired Bearing Rollers	-	■	-	-	-	-
> Insulated Door Track	-	■	-	-	-	-
> Magnetic Sliding Door Seals	-	■	-	-	-	-
Power Supply, 15 Amp Dedicated Circuit	■	■	■	■	■	■
Dependable Series™ 36-48-60 Month Limited Warranty	■	■	■	■	■	■
Additional Shelves	□	□	□	□	□	□
Additional Shelf Clips	□	□	□	□	□	□
Pan Rack Stainless Steel - Set of Four (4) with Clips	□	-	□	-	□	-
Caster Set Swivel, Low Profile, Two Locking 3.75 Inch	□	□	□	□	□	□
Leg Set SST 6"H Adjustable	□	□	□	□	□	□
Leg Set Seismic-Security SST 6"H Adjustable	□	□	□	□	□	□

■ Standard Feature □ Optional Feature - Not Applicable

DEPENDABLE SERIES



3/4/5 Limited Warranty

*36 Months Labour

*48 Months Parts

*60 Months Compressor

Contact Your Local Russell-Hendrix Location

VICTORIA, BC	250-386-3161
VANCOUVER, BC	604-253-6611
EDMONTON, AB	780-423-4221
CALGARY, AB	403-253-1383
SASKATOON, SK	306-652-7777
WINNIPEG, MB	204-775-8835
THUNDER BAY, ON	807-623-2544
LONDON, ON	519-679-9350
TORONTO, ON	416-207-9000
OTTAWA, ON	613-238-6555
MONTRÉAL, QC	514-382-1160
HALIFAX, NS	902-454-7461



Russell-Hendrix FoodService Equipment, Dependable Series™ & respective Graphic Designs are trademarks of Russell-Hendrix FoodService Equipment.

© HABCO Manufacturing Inc. "HABCO" & "Cassette" are registered trademarks of HABCO Manufacturing Inc. "Cold Space, Xterior, Energy Balanced" & Graphic Designs are trademarks of HABCO Manufacturing Inc. Used with Permission. Domestic & International Patents.

HABCO Management Systems are Certified to ISO 9001:2015. Russell Dependable Series™ Reach-Ins are commercially manufactured by HABCO.