



SE46HCSA

Double Solid Door Refrigerator


WIDTH ¹	DEPTH ²	HEIGHT ⁵	COLD SPACE™	ENERGY VOLUME	COOLING CAPACITY	ELECTRICAL ⁷	SHIPPING WEIGHT
47.5" 1207 mm	31" 788 mm	78" 1982 mm	46	78 cu. ft. 2.21 m ³	1/4 HP	115V / 60Hz / 4.3A	398 lbs. 181 kg.

¹ Add 19mm (3/4") for casters. ² Add 26mm (1") for power cord. ⁵ Add 121mm (4 3/4") for casters. ⁷ Commercial refrigerators and freezers are designed for maximum duty and require dedicated 15 amp electrical circuits to maintain warranty.

SE46HCSA: Designed to enhance the refrigerated storage or display experience to the highest standards of quality and performance.

Refrigeration:

- Self contained Cassette® forced-air refrigeration employs R290 hydrocarbon Natural Refrigerant within a sealed capillary tube system.
- Cassette® refrigeration is bottom-mounted and removable from the front for ease of maintenance. Refrigeration may be exchanged or upgraded without mechanic. Designed to operate at a set point between 34°F to 39°F (1°C - 4°C).
- Priority, directed air flow provides optimum cooling and energy efficiency within cabinet and exclusively at front of unit for optimized heat exchange ventilation.
- Finless, Free&Clear™ Condenser Coil maximizes air-flow over the compressor, reduces energy consumption and is non-clogging.
- Corrosion resistant coated evaporator coil.
- Automatic, stainless steel condensate control system.
- Quality, self-lubricating and sealed motors with streamlined air-flow provide quieter yet robust refrigeration.
- Equipped with ProcuTemp™ Energy Efficient Digital Controller featuring visual/audible product protection alarm.
- Controls refrigeration and displays according to simulated average product temperature to a display resolution of 1°C.



Cabinet:

- Exterior – stainless steel front and sides.
- Stainless Steel Interior stands up to rigours of everyday wear and tear.
- Ergonomic raised interior floor.
- Space Saving Design – air ventilation exclusively from the front of unit.
- Insulation – cabinet and solid doors are foamed-in-place with eco-conscious, polyurethane insulation.
- 5" Swivel Caster Kit Included.

Doors:

- Stainless steel with large grip, recessed handle.
- Self-Closing Swing Doors feature hold-open position, spring-back protection and door locks.
- Magnetic gaskets are single piece bead-mount construction easily removable for cleaning.

Lighting:


- Auto-Actuated Interior Lighting.

Storage:

- Six (6) white coated shelves 21 1/2"W x 20 1/2"D (547mm x 521mm), are NSF approved.
- Heavy duty aluminum shelving pilasters will not peel or chip adjustment of 1/2" (13mm) increments.
- NSF-7 compliant for storage and display of open food product.

Electrical:

- Factory power cord installed for connection to a sole-use (dedicated) 115V/60Hz/1-Phase, 15 Amp circuit.



HABCO MANUFACTURING INC. 501 GORDON BAKER ROAD, TORONTO, ONTARIO, CANADA, M2H 2S6
 Toll Free CAN: 1-800-387-5398 USA: 1-800-448-0244 Fax: 416-491-6982 www.habcomfg.com